

HIGH SOLIDS METALLISED FLOOR POLISH – 1106

A metallised polish for extreme strength and durability, coupled with ease of removability.

- ❖ Non-yellowing cross linked polymer film – does not discolour even the lightest floor.
- ❖ Produces a deep shine with excellent slip resistance.
- ❖ Responds brilliantly to all spray burnishing techniques.

USES:

For all linoleum, PVC, rubber, sealed wood, terrazzo and thermoplastic floors.

N.B: Not suitable for unsealed wood, unsealed cork or laminate flooring.

DIRECTIONS:

High Solids Metallised Floor Polish must be applied to a clean, grease-free floor.

Strip old polish with Ammonia Free Metallised Floor Polish Stripper then rinse thoroughly with clean water and allow to dry.

Apply a thin, even film of the product using a clean, lint-free mop or applicator.

Apply a second coat when the first is dry (approximately 30 minutes).

May be buffed (as required) to enhance gloss.

COVERAGE: 60 square metres per litre.

MAINTENANCE: Damp Mopping – as required, using Lemon Jell or Universal Cleaner.

Spray Cleaning/Burnishing – regular use of Floor Maintainer will enhance appearance and life expectancy.

TECHNICAL SPECIFICATION:

Composition: A low viscosity, opaque, cream coloured liquid, which has a slight sweet odour. It is a blend of acrylic and ethylene polymer dispersions, anionic and non-ionic wetting agents, plasticisers, coalescents, humectants and a metal salt for cross-linking.

Appearance: Translucent emulsion

Colour: Cream

Viscosity: <10 cps

Density: 1.025

pH: 8.0 – 8.2

Activity: 18%

Fragrance: Characteristic slightly sweet

Stability: 2 years in unopened containers

Storage: Protect from freezing

Safety: Keep out of the reach of children.

Safety data sheet available for professional user on request.