

TECHNICAL DATA SHEET

SUPER STRENGTH TRAFFIC FILM REMOVER – 0923

Developed for both hot and cold pressure wash applications.
Suitable for hard or soft water.

- ❖ Fast acting
- ❖ Free rinsing
- ❖ Highly concentrated
- ❖ Economical

USES:

Concentrated traffic film remover for use through hot or cold pressure wash equipment. Suitable for use in the transport industry eg, buses, box vans, curtain sided vehicles, tankers, earth moving equipment, cars etc.

DIRECTIONS:

Pre-dilute with up to 1:8 parts water – light soiling.

1:4 parts water – heavy soiling

1:2 parts water – chassis cleaning prior to pouring into detergent feed tank. Adjust feed rate as required. Typical final dilution 2%.

Lightly spray vehicle and allow to soak for up to 5 minutes. Rinse thoroughly using high pressure spray.

Do not use on aluminium or galvanised surfaces.

Do not allow the product residue to dry out on the vehicle or staining may occur. Always rinse thoroughly after use.

TECHNICAL SPECIFICATION:

Composition	A blend of alkaline builders, non-ionic and amphoteric surfactants, sequestents, soil suspending agents and solubilisers.
Appearance	Clear liquid
Colour	Dark red
Cloud Point	45
Density	1.073
pH	>13.5
Fragrance	Unfragranced
Stability	Two years in unopened containers

Safety: Keep out of the reach of children.