

TECHNICAL DATA SHEET

WAX, OIL AND GREASE REMOVER - 1113

Heavy duty spirit based oil and grease remover.

- ❖ Removes wax build-up from floors.
- ❖ Engine and industrial plant cleaner.
- ❖ Removes tar and bitumen easily.

USES:

Wax, Oil and Grease Remover is ideal for removal of old wax from floors. It may also be used as a brush or spray on, hose off degreasant for engines and greasy metal parts. The product also removes oil and diesel spillages from concrete and brick floors.

DIRECTIONS:

Floor wax removal – apply product neat. Allow to penetrate for ten minutes. Machine scrub preferably adding water to form an emulsion. Mop up or suction dry. Rinse and allow to dry before reapplying wax polish.

Degreasing – spray on. Brush if necessary to loosen impacted dirt. Hose off.

NB: Wax, Oil and Grease Remover should not be used on solvent sensitive surfaces e.g. thermoplastic or bitumastic.

TECHNICAL SPECIFICATION:

Composition: A blend of refined aliphatic and aromatic hydrocarbons and biodegradable emulsifiers.

Appearance: Clear liquid

Colour: Pale Amber Liquid

Density: 0.788

Fragrance: Solvent odour

Stability: Two years in unopened container.

Safety: Keep out of the reach of children.

In case of contact with eyes, rinse immediately with plenty of water and seek medical advice. Use only in well-ventilated areas. If swallowed, do not induce vomiting; seek medical advice immediately and show the container or label. Wear suitable gloves and eye/face protection.

Flammable. Harmful to aquatic organisms, may cause long-term adverse effects in the aquatic environment. Repeated exposure may cause skin dryness or cracking. Harmful; may cause lung damage if swallowed