

BASE COAT FLOOR SEAL – 1115

Acrylic base coat seal.

- ❖ Non-yellowing polymer film – does not discolour even the lightest floor.
- ❖ Penetrates and seals porous floors.
- ❖ Provides an ideal base for emulsion application.
- ❖ Resistant to polish strippers.

USES:

For all linoleum, PVC, rubber, terrazzo and thermoplastic floors.

N.B: Do not use on unsealed wood and cork floor coverings.

DIRECTIONS:

Product must be applied to a clean, grease-free floor.

Apply a thin, even film of seal using a clean, lint-free mop or applicator.

Apply a second coat when the first is dry (approximately 30 minutes).

COVERAGE RATE: 50 square metres per litre.

MAINTENANCE: Base Coat Floor Seal is formulated as a sealer coat and does not have a high resistance to wear. It must be finished by the application of Super High Solids Metallised Floor Polish or other metallised polymer emulsion and normal maintenance techniques employed.

TECHNICAL SPECIFICATION:

Composition: A blend of acrylic copolymers, resins incorporating wetting agents and film forming aids in a stable water based emulsion.

Appearance: Translucent emulsion.

Colour: Cream

Viscosity: <10 cps

Density: 1.012

pH: 9.2

Activity: 16%

Fragrance: Characteristic slightly sweet.

Stability: Two years in unopened container.

Storage: Protect from freezing.

Safety: Keep out of the reach of children.

Safety data sheet available for professional user on request.